

NORTHWEST LININGS DAILY LANDFILL COVER

NTS

Northwest Linings & Geotextile Products, Inc. (NWL) is not a licensed engineering firm and does not practice engineering or provide engineering services. **NWL does not make any representation or warranties, express or implied, as to any drawings, or the suitability of any of the drawings for a particular use or purpose. Without limiting the foregoing, NWL makes no representation or warranty that the drawings are appropriate for any particular installation.** Only a registered professional engineer who has specialized knowledge of a particular project and the needs and requirements of such project can determine what specific design, engineering or installation detail is best suited for each project.


DAILY COVER SPECIFICATIONS

- PermeaTex 2315 Woven Geotextile 13.1' wide
- Double Stitched J-Seams Around Perimeter
- Reinforced corners to triple layer and go 10' away from each corner 150'x225' ---- use 13.1' wide and sew together 18 panels to make 225'
- Sew straps (black belting) every 23' OC along all sides (30" long and sewn 6" into reinforced edge) see additional detail
- Sew 1/4" rope into perimeter around all sides encased in 6" wide 2315 fabric.
- Need HDPE plate for reinforcing corners all four corners with 2 bolts and Quicklink do this on all four corners
- Use orange Belton 36" fabric cut into 12" strips w/ hot knife and sew along 150' sides
- Precut 36" orange in straight lines in 150' increments to make 450 total LF – (do 4 times)

SHEET NO.

1 of 2

DETAIL



NORTHWEST LININGS & GEOTEXTILE PRODUCTS, Inc.

www.northwestlinings.com
21000 77TH AVE. SOUTH
KENT, WA. 98032
(253) 872-0244 (253) 872-0245 FAX

JOB NAME:

JOB NO.

5 28 01

DATE:

5 28 01

CHECKED:

5 28 01

BY:

5 28 01

SCALE: